

Make an impression with bound documents

AP-2 Ultra

Punches - Modular and Productive

The AP-2 Ultra automatic punch easily handles a wide variety of sheet sizes, punch styles, paper stocks and index tabs. It can easily punch intermixed index tabs and irregularly sized covers as well as coated, laminated, glossy, and heavier stocks. The electronic control panel enables the user to set the speed for each job.

Features & Benefits

- Sheet size: Punched edge: 139mm to 304mm, Unpunched edge: 139mm to 298mm.
- Punch productivity: Variable, up to 56,000 sheets/hour (40,000 sheets per/hour average)*
- Paper Stock: 80gsm to 163gsm index, including index tabs
- Punch capacity: Feed hopper and output stacker hold 2,500 sheets of 80 gsm bond or equivalent
- Punching die patterns: CombBind®, WireBind, ColorCoil®, VeloBind®, 3-5-7 hole and more.
- Edge guide adjustment knobs allow effortless sheet changes without tools
- Separate paper loader and output stacker: Enables you to feed paper / unload punched paper without having to stop the machine
- Adjustable pick feeder accommodates various paper stocks
- Convenient built-in die storage compartment: Ensures dies are always at hand
- Interchangeable die sets slide in place quickly without tools
- LCD Display: Informs operator of status at all times
- Emergency Stop Button: Safety operation
- CombBind®, WireBind, StripBind™, CoilBind™, 2-4/3-5-7
 Binding
- Punched edge: 139mm to 304mm, Unpunched edge: 139mm to 298mm.
- Variable, up to 56,000 sheets/hour (40,000 sheets per/hour average)*



Technical Specifications

Binding style	CombBind®, WireBind, StripBind™, CoilBind™, 2-4/3-5-7 Binding		
Document size	Punched edge: 139mm to 304mm, Unpunched edge: 139mm to 298mm.		
Punch capacity 80g	Variable, up to 56,000 sheets/hour (40,000 sheets per/hour average)*	Dimension (mm) W x D x H	635 x 864 x 1346
Method of operation	Electric	Weight (kg)	136
Power Consumption (watt)	506		